

## Haulick RV 160-1600 R Delme presi PR2467, kullanılmış



**manufacturer :** Haulick

**Product number:**  
PR2467

### Description

#### Punching press

|                     |         |
|---------------------|---------|
| Manufacturer        | Haulick |
| Year of manufacture | 1980    |
| Last revision       |         |
| Comment             |         |

### Technical Data

#### Press design

|                               |               |
|-------------------------------|---------------|
| Number of suspensions         | 2             |
| Number of slide actions       | 1             |
| feedstock transport direction | left to right |
| Press                         |               |
| Force                         | 1600 kN       |
| Table surface (left-right)    | 1500 mm       |

| Press design                                    |          |
|---|----------|
| Table surface (front-back)                      | 1200 mm  |
| Thickness of bolster plate                      | 240 mm   |
| Opening in bed (left-right)                     | 1300 mm  |
| Opening in bed (front-back)                     | 300 mm   |
| Number of T-slots                               | 8        |
| Slide   |          |
| Slide force                                     | 1600 kN  |
| Table surface (left-right)                      | 1550 mm  |
| Table surface (front-back)                      | 1200 mm  |
| Stroke  | 120 mm   |
| Stroke rate max.                                | 150 /min |
| Slide adjustment                                | 150 mm   |
| Stroke rate min,                                | 15 /min  |
| Stroke rate max.                                | 150 /min |
| Tool assembly dimensions                        |          |
| Shut height (stroke down, adjustment up) BDC    | 470 mm   |
| Distance between columns (H-frame)              | 1600 mm  |
| Passline opening (free passage in side columns) | 700 mm   |
| Free passe between side columns (height)        | 700 mm   |

| Decoiler            |            |
|---------------------|------------|
| Manufacturer        | Schleicher |
| Year of manufacture | 1974       |

## Technical Data

## Decoiler

|                                |              |
|--------------------------------|--------------|
| Coil weight max.               | max 5 t      |
| sheet width max.               | 650 mm       |
| Diameter of coil max.          | 1500 mm      |
| Mandrel expansion range        | 450 - 520 mm |
| Leveller unit                  |              |
| sheet thickness                | 0.5 ÷ 2.5 mm |
| Number of leveller rolls       | 6            |
| Number of infeed/outfeed rolls | 2            |
| Feed velocity                  | 6 - 30 m/min |
| Loop controls                  | yes          |
| Strip-feeder                   |              |
| Feeding step max               | 9999.9 mm    |
| Pilot release system           | yes          |
| Total height                   | 4500 mm      |
| Weight                         | 26 t         |
| Delivery time                  | immediately  |
| Price                          | on request   |

