fissmachines.com
friedrich // industrial // solutions // services

FISS GmbH
Hauptstraße 8
73650 WINTERBACH
GERMANY

Phone +49 (0)7181 60696-0
Fax: +49 (0)7181 60696-00
E-Mail info@fissmachines. com

Managing Directors: Klaus Friedrich, Michael Friedrich
Amtsgericht Stuttgart HRB 783559
USt-ID-No.:DE35 0949 264

Haulick RV 160-1600 R Delme presi PR2467, kullanılmış



manufacturer : Haulick

Product number:
PR2467

Description

Punching press	
Manufacturer	Haulick
Year of manufacture	1980
Last revision	
Comment	

Technical Data

Press design	
Number of suspensions	2
Number of slide actions	1
feedstock transport direction	left to right
Press	
Force	1600 kN
Table surface (left-right)	1500 mm

fissmachines.com
friedrich // industrial // solutions // services

FISS GmbH
Hauptstraße 8
73650 WINTERBACH
GERMANY

Phone +49 (0)7181 60696-0
Fax: +49 (0)7181 60696-00
E-Mail info@fissmachines. com

Managing Directors: Klaus Friedrich, Michael Friedrich
Amtsgericht Stuttgart HRB 783559
USt-ID-No.:DE35 0949 264

Press design	
Table surface (front-back)	1200 mm
Thickness of bolster plate	240 mm
Opening in bed (left-right)	1300 mm
Opening in bed (front-back)	300 mm
Number of T-slots	8
Slide	
Slide force	1600 kN
Table surface (left-right)	1550 mm
Table surface (front-back)	1200 mm
Stroke	120 mm
Stroke rate max.	150 /min
Slide adjustment	150 mm
Stroke rate min,	15 /min
Stroke rate max.	150 /min
Tool assembly dimensions	
Shut height (stroke down, adjustment up) BDC	470 mm
Distance between columns (H-frame)	1600 mm
Passline opening (free passage in side columns)	700 mm
Free passe between side columns (height)	700 mm

Decoiler	
Manufacturer	Schleicher
Year of manufacture	1974

Technical Data

fissmachines.com
friedrich // industrial // solutions // services

FISS GmbH
Hauptstraße 8
73650 WINTERBACH
GERMANY

Phone +49 (0)7181 60696-0
Fax: +49 (0)7181 60696-00
E-Mail info@fissmachines. com

Managing Directors: Klaus Friedrich, Michael Friedrich
Amtsgericht Stuttgart HRB 783559
USt-ID-No.:DE35 0949 264

Decoiler	
Coil weight max.	max 5 t
sheet width max.	650 mm
Diameter of coil max.	1500 mm
Mandrel expansion range	450 - 520 mm
Leveller unit	
sheet thickness	0.5 ÷ 2.5 mm
Number of leveller rolls	6
Number of infeed/outfeed rolls	2
Feed velocity	6 - 30 m/min
Loop controls	yes
Strip-feeder	
Feeding step max	9999.9 mm
Pilot release system	yes
Total height	4500 mm
Weight	26 t
Delivery time	immediately
Price	on request



